Product data sheet

Specifications



Lower sup. Ver. Busbars In 3200A 10mm bars. Bar distance 115mm. For 800mm witdhs

NSYAS800L

Main

Range	PanelSeT
Accessory / separate part category	Support accessory
Product or component type	Bar support
Anwendung	Multi-purpose Prisma application
Enclosure nominal dimensions	-
Mounting location	Bottom
Busbar position	Vertical
Range compatibility	Linergy Linergy LGYE Linergy Linergy BS Prisma Prisma PH

Complementary

Cubicle-device connection	Linergy LGYE lateral busbar Linergy BS lateral busbar
Device composition	fixing elements 1 insulating bar support 1 metal support
Quantity per set	Set of 1
Material	Bar support: plastic Metal support: steel
Fixing mode	By fixing element - bottom frame of enclosure location
Height	66 mm
Width	Fixing centers: 750 mm Nominal: 800 mm
Depth	39 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.000 cm
Package 1 Width	10.000 cm
Package 1 Length	78.500 cm
Package 1 Weight	2.188 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	16

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Height	40.000 cm
Package 2 Width	60.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	32.000 kg

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**16 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**10 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.4 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0.5 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**0 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**5 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**

Use Again

Repack and remanufacture

Recyclability potential, in %	**98**
End of life manual availability	**No need of specific recycling operations**
Take-back	**No**