
Product data sheet

Specifications



2 ver. busbar sup. In 3200A 10 mm bars. Bars distance 115mm. For 800mm widths

NSYBVS800L

Main

Range	PanelSeT
Accessory / separate part category	Busbar accessory
Product or component type	Busbar support
Anwendung	Multi-purpose Prisma application
Enclosure nominal dimensions	-
Mounting location	On structure of enclosure
Busbar position	Vertical
Range compatibility	Linergy Linergy LGYE Linergy Linergy BS Prisma Prisma PH

Complementary

Cubicle-device connection	Linergy LGYE lateral busbar - fixed Linergy BS lateral busbar - fixed
Device composition	fixing elements 1 metal support 2 insulating bar support
Quantity per set	Set of 1
Material	Bar support: plastic Metal support: steel
Fixing mode	By fixing element
Width	Fixing centers: 750 mm Nominal: 800 mm
Depth	39 mm
[In] rated current	3200 A

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.000 cm
Package 1 Width	11.000 cm
Package 1 Length	78.000 cm
Package 1 Weight	2.882 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	50

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Height	50.000 cm
Package 2 Width	100.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	157.000 kg

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**20 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**13 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**0.6 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0.6 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**0 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**7 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**

Use Again

Repack and remanufacture

Recyclability potential, in %	**98**
End of life manual availability	**No need of specific recycling operations**
Take-back	**No**