
Product data sheet

Specifications



Post fixing device WM PanelSeT, length 500. For post max 675. Max. Load:100kg.

NSYSFPSC50

Main

Range	PanelSeT
Accessory / separate part category	Fixing accessory
Product or component type	Post fixing device
Device application	Multi-purpose
Enclosure nominal dimensions	-
Mounting location	Rear of enclosure
Range compatibility	PanelSeT S3D PanelSeT SBM SBM PanelSeT CRN
Device composition	fixing elements 2 support rail 2 strip
Quantity per set	Set of 1

Complementary

Material	Galvanised steel
Fixing mode	By fixing element - screw type M8 - to the inserts in the rear of the enclosure location Minimum diameter 150 mm Maximum diameter 215 mm
Permanent permissible load	100 kg
Height	45 mm
Width	495 mm
Depth	32.5 mm
Net weight	2.588 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.500 cm
Package 1 Width	20.000 cm
Package 1 Length	51.000 cm
Package 1 Weight	2.588 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	200
Package 2 Height	120.000 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 2 Width	100.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	520.000 kg

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	Free of Substances of Very High Concern above the threshold

Use Again

Repack and remanufacture

End of life manual availability	No need of specific recycling operations
Take-back	No