Product data sheet

Specifications



Climasys Ultra thin resistance heater low starting current 50W 120V 200x320mm

NSYCRS50W120V

Discontinued on: Dec 31, 2021

Discontinued

Main

Range	ClimaSys
Product name	ClimaSys CR
Product or component type	Ultra thin resistance heater
Power range	50 W
Input voltage	120 V AC 50/60 Hz
Electrical connection	Cable length: 2 m

Complementary

Operating position	Vertical Horizontal
Ambient air temperature for operation	-60…70 °C
Temperature setting range	-40…70 °C
Material	Silicone rubber
Height	External: 200 mm
Width	External: 320 mm
Depth	External : 1.6 mm
Device composition	6 self-adhesive Velcro pads 6 plastic spacers 4 Telequick nuts 4 clip-on nuts fixing accessories
Condition of use	Electrical protection is needed Air sealed enclosure Heaters must be installed with a thermal controller
fixing mode	By 4 screws
Mounting support	DIN rail Standard mounting plate Telequick mounting plate Adhesive Velcro

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty (in months)	18

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances

EU RoHS Directive	Compliant

Use Again

Repack and remanufacture

WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins