# Product data sheet

Specifications



## Control window with aluminum frame and 3 mm acrylic window 500 x 400 mm

NSYCW54

## Main

| | |
|---|---|
| **Range** | PanelSeT |
| **Accessory / separate part category** | Installation accessory |
| **Product or component type** | Window |
| **For enclosure nominal dimensions** | - |
| **Range compatibility** | PanelSeT S3D<br>PanelSeT CRN |
| **Mounting location** | Installation on door or panel |
| **Device composition** | 2 hinge<br>1 lock<br>1 fixings and drilling template<br>1 frame with window |
| **Material** | Transparent acrylic<br>aluminium |
| **Lock type** | Closure by lock |
| **Number of locks** | 1 |
| **Key number** | 2233X |

## Complementary

| | |
|---|---|
| **Height** | 500 mm |
| **Width** | 400 mm |
| **Depth** | 77 mm |
| **Type of installation** | Indoor installation |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Number of Units in Package 1** | 1 |
| **Package 1 Height** | 56.000 cm |
| **Package 1 Width** | 44.000 cm |
| **Package 1 Length** | 12.000 cm |
| **Package 1 Weight** | 4.010 kg |
| **Unit Type of Package 2** | P12 |
| **Number of Units in Package 2** | 15 |
| **Package 2 Height** | 96.000 cm |
| **Package 2 Width** | 80.000 cm |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Package 2 Length** | 120.000 cm |
| **Package 2 Weight** | 44.250 kg |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Total lifecycle Carbon footprint | **29 kg CO2 eq.** |
| Carbon footprint of the manufacturing phase [A1 to A3] | **17 kg CO2 eq.** |
| Carbon footprint of the distribution phase [A4] | **0.8 kg CO2 eq.** |
| Carbon footprint of the installation phase [A5] | **0.9 kg CO2 eq.** |
| Carbon footprint of the use phase [B2, B3, B4, B6] | **0 kg CO2 eq.** |
| Carbon footprint of the end-of-life phase [C1 to C4] | **9 kg CO2 eq.** |
| Environmental Disclosure | **Product Environmental Profile** |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | **No** |
| Packaging without single use plastic | **No** |
| SCIP Number | **86c971db-94b7-45f1-bdf1-8c503ea9309d** |
| EU RoHS Directive | **Compliant By Exemption** |
| REACh Regulation | **Reference contains Substances of Very High Concern above the threshold** |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Recyclability potential, in % | **98** |
| End of life manual availability | **No need of specific recycling operations** |
| Take-back | **No** |