NAPA-RD

VP886600



Electromechanical time switch, 230 Vac, 96-tripper, daily programming. The device features a power reserve thanks to a built-in rechargeable, non-replaceable battery. Panel-mounted installation.

General features

- Three-position selector switch:
  - 0 permanently off
  - I permanently on
  - 🕒 automatic operation via trippers
- Accessory supplied for wall-mounted or DIN-rail mounted installation
- External dial with captive trippers
- Internal dial with hands for current time indication

Technical specifications

Power supply	
Power supply	230 Vac (-10% ÷ +10%)
Frequency	50 / 60 Hz
Absorption	1.8 VA
Power reserve	100 hours after an uninterrupted charge of 48 hours
Parameter settings	
Programming	Daily
Minimum manoeuvring time	15 min
Measure	
Watch accuracy	± 1 second/day at 23 °C
Operating conditions	
Operating temperature range	-10 ÷ 45 °C
Insulation class	II
Connectable loads	
Incandescent lamps	3000 W
Fluorescent lamps (neon)	1200 VA
Halogen lamps (low voltage)	2000 VA


Vemer S.p.A. declines all responsibility for the use of the products for purposes other than those for which they are intended, as indicated in the technical documentation. Vemer S.p.A. reserves the right to make, without prior notice, such changes as may, in its sole discretion, improve the technical and functional characteristics of the products and the related production logic. The technical characteristics and images of the products indicated are given for information only and are not binding in any way, since they may be modified without prior notice.

Revision date: 2026-02-02


Connectable loads	
Halogen lamps (230 V)	3000 W
Low Consumption Lamps (CLF)	1000 VA, 900 VA
LED lamps	200 VA
Viewing	
Dial	24 hours
Number of trippers	96
Outputs	
Relay number	1
Relay capacity at 250 Vac	16 (4) A
Terminations	
Maximum cable cross-section	4 mm²
Mechanical features	
Protection degree	IP20
Physical features	
Device command	Trippers
Overall dimensions	
Height (A)	72 mm
Width (B)	72 mm
Depth (C)	38 mm

Dimensions


Front View



Side View




Drilling template for rear panel / panel mounting




Rear-panel mounting

Vemer S.p.A. declines all responsibility for the use of the products for purposes other than those for which they are intended, as indicated in the technical documentation. Vemer S.p.A. reserves the right to make, without prior notice, such changes as may, in its sole discretion, improve the technical and functional characteristics of the products and the related production logic. The technical characteristics and images of the products indicated are given for information only and are not binding in any way, since they may be modified without prior notice.

Wiring diagram



Graphic details



Model variants

NAPA-RED

Panel-mounted electromechanical time switch with trippers and daily programming.

Reference standards

Compliance with Community Directives:

• 2014/35/UE (LVD) • 2014/30/UE (EMCD) • 2011/65/UE e 2015/863/UE (ROHS)

is declared with reference to the following Standards:

• EN IEC 60730-2-7 • EN IEC 63000

Vemer S.p.A. declines all responsibility for the use of the products for purposes other than those for which they are intended, as indicated in the technical documentation. Vemer S.p.A. reserves the right to make, without prior notice, such changes as may, in its sole discretion, improve the technical and functional characteristics of the products and the related production logic. The technical characteristics and images of the products indicated are given for information only and are not binding in any way, since they may be modified without prior notice.