memo Y

VE340600



Digital time switch with 230 Vac power supply and DIN rail installation with 2 module size. Device offers daily/weekly/monthly/yearly programming and includes 1 relay. Thanks to the integrated NFC interface and the Memo application, smartphones and tablets can be easily paired with the device, allowing its functions to be managed remotely, with maximum convenience and without the need for wire connections.

General features

- Large backlit display for viewing date, time, and relay status
- Battery life: 5 years (with service flap for replacement)
- Sealable keyboard cover
- Application for iOS and Android systems
- Programs: ON, OFF, pulse (1–59 seconds), holiday
- Random output switching function
- Manual relay override (temporary or permanent)
- Automatic daylight saving time update
- Low battery warning
- NFC interface
- Keypad lock function with password to prevent modifications by unauthorised people
- Menu in 5 languages: Italian, English, Spanish, German, French

Technical specifications

Power supply	
Power supply	230 Vac (-10% ÷ +10%)
Frequency	50 / 60 Hz
Absorption	8 (2) VA (W)
Buffer battery type	CR-2032 Lithium 3 V (NOT rechargeable)
Battery autonomy	5 years
Power reserve	1 minute
Parameter settings	
Programming	Hourly (Daily / Weekly / Yearly)
Programming resolution	1 minute
Number of storable programmes (events)	120
Measure	
Watch accuracy	± 0.5 seconds/day at 25 °C

Vemer S.p.A. declines all responsibility for the use of the products for purposes other than those for which they are intended, as indicated in the technical documentation. Vemer S.p.A. reserves the right to make, without prior notice, such changes as may, in its sole discretion, improve the technical and functional characteristics of the products and the related production logic. The technical characteristics and images of the products indicated are given for information only and are not binding in any way, since they may be modified without prior notice.

Revision date: 2026-02-02

Functions	
Automatic daylight saving/standard time changeover	✓
Keypad lock function	✓
Manageable by application	✓
Operating conditions	
Operating temperature range	-20 ÷ 50 °C
Storage temperature range	-25 ÷ 70 °C
Connectable loads	
Incandescent lamps	2000 W
Fluorescent lamps (neon)	1000 VA
Halogen lamps (230 V)	2000 W
Low Consumption Lamps (CLF)	200 W
LED lamps	200 W
Approvals and certifications	
ENEC approval	✓
Outputs	
Relay number	1
Relay type	Heat exchange
Relay capacity at 250 Vac	16 (10) A
Mechanical features	
Protection degree	IP20 IP41 (on the front)
Physical features	
Device command	Keys
Backlighting	✓
Overall dimensions	
Height (A)	87 mm
Width (B)	36 mm
Depth (C)	65 mm

Vemer S.p.A. declines all responsibility for the use of the products for purposes other than those for which they are intended, as indicated in the technical documentation. Vemer S.p.A. reserves the right to make, without prior notice, such changes as may, in its sole discretion, improve the technical and functional characteristics of the products and the related production logic. The technical characteristics and images of the products indicated are given for information only and are not binding in any way, since they may be modified without prior notice.

Dimensions

Front View



Side View



Wiring diagram



Remote control

Fully manageable via smartphone and tablet app

Memo

memo

GET IT ON Google Play

Download on the App Store

Memo is the smart application designed to control and programme Vemer digital watches. Depending on the model, the watch can be connected to smartphones and tablets via the NFC interface or Bluetooth connection. The Memo application's intuitive interface ensures practical and immediate use of the included functionalities, simplifies the management of device settings and its programming, and offers the user a wide range of customisation possibilities.

App features

- **Program management**
  Allows creating, editing, and renaming programs directly on the smartphone.
- **Copy / Paste programs**
  Allows transferring created programs to multiple timers of the same model. Acquire programs from one timer and copy them to other timers of the same model (copy / paste).
- **Relay Outputs**
  Allows manual switching of relay outputs.
- **GPS**
  Allows configuring the geographic coordinates on the timer.
- **Date / Time**
  Allows configuring the date and time on the timer.
- **Random output switching function**
  It allows you to switch the relay outputs automatically at regular intervals.

Vemer S.p.A. declines all responsibility for the use of the products for purposes other than those for which they are intended, as indicated in the technical documentation. Vemer S.p.A. reserves the right to make, without prior notice, such changes as may, in its sole discretion, improve the technical and functional characteristics of the products and the related production logic. The technical characteristics and images of the products indicated are given for information only and are not binding in any way, since they may be modified without prior notice.

Product variants

memo Y2

VE342200

DIN-rail mounted digital electronic time switch with daily, weekly, monthly or annual programming, 2-DIN module, 230 Vac, 2 relays, NFC.

Reference standards

Compliance with Community Directives:

• 2014/53/UE (RED) • 2011/65/UE e 2015/863/UE (ROHS)

is declared with reference to the following Standards:

• EN IEC 60730-2-7 • EN 50364 • ETSI EN 300 330 • ETSI EN 301 489-1 • ETSI EN 301 489-3 • EN IEC 63000

Vemer S.p.A. declines all responsibility for the use of the products for purposes other than those for which they are intended, as indicated in the technical documentation. Vemer S.p.A. reserves the right to make, without prior notice, such changes as may, in its sole discretion, improve the technical and functional characteristics of the products and the related production logic. The technical characteristics and images of the products indicated are given for information only and are not binding in any way, since they may be modified without prior notice.