TU 30 600/5A

VM711900



Through-bar current transformer for AC devices, with x/5 A transformation ratio and suitable for DIN-rail or panel mounting (using the supplied supports).

General features

- Busbar passage: 20–25–30 mm
- Cable passage: Ø 22 mm
- Double clamp for secondary
- Opening (hole) for cable or busbar passage (primary)

Technical specifications

Power supply	
Frequency	50 / 60 Hz
Measure	
Transformation ratio	600/5 A
Functional characteristics	
Short-term thermal current	1,2 In A A
Safety factor	<5
Maximum operating voltage	720 V
Rated withstand voltage at 50 Hz for 1 min	3 kV
Rated power Class 0.5	5 VA
Rated power Class 1	7.5 VA
Rated power Class 3	10 VA
Operating conditions	
Operating temperature range	-10 ÷ 50 °C
Physical features	
Insulated housing	✓
Overall dimensions	
Height (A)	79 mm
Width (B)	60 mm

Vemer S.p.A. declines all responsibility for the use of the products for purposes other than those for which they are intended, as indicated in the technical documentation. Vemer S.p.A. reserves the right to make, without prior notice, such changes as may, in its sole discretion, improve the technical and functional characteristics of the products and the related production logic. The technical characteristics and images of the products indicated are given for information only and are not binding in any way, since they may be modified without prior notice.

Revision date: 2026-02-02

TU 30 600/5A

VM711900

Overall dimensions	
Depth (C)	63 mm

Dimensions

Front View



Side View



Hole Detail



Wiring diagram



When connecting all current transformers, it is important to respect the current directions.

- Primary: P1/K to P2/L
- Secondary: S1/k to S2/l

Note: The current-carrying capacity of the current transformer must correspond to the full scale of the device.

Product variants

TU 30 150/5A
VM705100
Through-bar current transformer 150/5 A

TU 30 200/5A
VM706900
Through-bar current transformer 200/5 A

TU 30 250/5A
VM707700
Through-bar current transformer 250/5 A

TU 30 300/5A
VM708500
Through-bar current transformer 300/5 A

TU 30 400/5A
VM709300
Through-bar current transformer 400/5 A

TU 30 500/5A
VM710100
Through-bar current transformer 500/5 A

Reference standards

Compliance with Community Directives:

• 2014/35/UE (LVD) • 2014/30/UE (EMCD) • 2011/65/UE e 2015/863/UE (ROHS)

is declared with reference to the following Standards:

• EN 61010-1 • EN 61869-2 • EN IEC 61000-6-2 • EN IEC 61000-6-3 • EN IEC 63000

Vemer S.p.A. declines all responsibility for the use of the products for purposes other than those for which they are intended, as indicated in the technical documentation. Vemer S.p.A. reserves the right to make, without prior notice, such changes as may, in its sole discretion, improve the technical and functional characteristics of the products and the related production logic. The technical characteristics and images of the products indicated are given for information only and are not binding in any way, since they may be modified without prior notice.

Revision date: 2026-02-02