Analog testers

VE 381

Pocket tester to measure direct and alternating voltage, direct current, resistance, battery charge.

- Operating conditions:
  - temperature range: +5 °C ÷ +40 °C
  - relative humidity: < 80%
- Power supply: 1 battery 1.5 V AA type
- Fuse: 0.5 A / 250 V (5x20 mm)
- Dimensions: 30x60x95 mm
- Weight: 100 g
- Included accessories: battery, spare fuse, measurement points, instructions for use



Code	Model	Description
VE367900	VE 381	Analog pocket tester

TECHNICAL INFORMATION

Function		Capacity	Full scale precision
Voltage	DC	2.5/10/50/250/500 V	± 4%
Voltage	AC	10/50/250/500 V	± 5%
Current	DC	0.5/10/250 mA	± 4%
Resistance	Ω	Rx10/Rx1k	
		(500 Ω f.s.)	
Decibel	dB	-20 ÷ +56	
		on all scales in V AC	
Batteries test	BAT	1.5 V	

REFERENCE STANDARDS

Compliance with Community Directives:
2006/95/EC (Low Voltage) and 2004/108/EC (E.M.C.)
is declared with reference to the following standards:
• Safety: EN 61010-1
• E.M. Compatibility: EN 61000-6-2 and EN 61000-6-4