TM NTC-P7A

VM621000



Digital panel thermometer (72x72) for temperature measurement in applications such as refrigerated counters, cold rooms and ambient temperature monitoring. The device can be connected to NTC thermistors.

General features

- Possibility of viewing minimum and maximum temperature values
- Possibility of adjusting probe calibration OFFSET
- Possibility of changing the temperature unit between °C and °F
- Possibility of adjusting update speed for measurement display
- Possibility of setting an access password to protect stored settings
- Acoustic and visual alarm signalling for probe malfunction or disconnected sensor cable

Technical specifications

Power supply	
Power supply	24 / 230 Vac (-10% ÷ +10%)
Frequency	50 / 60 Hz
Absorption	4.5 VA
Measure	
Temperature display resolution	0.1 (for values in the range -9.9 ÷ 99.9) °C 1 (for values <-9,9 and > 99.9) °C
Temperature measurement accuracy	± 0.5 % of full scale value ± 1 digit °C
Functions	
Probe alarm buzzer	✓
Functional characteristics	
Temperature display range	-40 ÷ 110 °C
Operating conditions	
Operating temperature range	0 ÷ 50 °C
Relative humidity	< 80% RH
Storage temperature range	-25 ÷ 70 °C
Storage humidity range	< 80% RH

Vemer S.p.A. declines all responsibility for the use of the products for purposes other than those for which they are intended, as indicated in the technical documentation. Vemer S.p.A. reserves the right to make, without prior notice, such changes as may, in its sole discretion, improve the technical and functional characteristics of the products and the related production logic. The technical characteristics and images of the products indicated are given for information only and are not binding in any way, since they may be modified without prior notice.

Revision date: 2026-02-02

TM NTC-P7A

VM621000

Viewing	
Display	Red LEDs
Digits number	3
Digits size	14 mm
Display range	-99 ÷ 800 °C
Inputs	
Number of connectable probes	1
Type of connectable probes	NTC (10 kΩ at 25 °C)
Mechanical features	
Protection degree	IP54 (on the front) IP20 (on terminals)
Overall dimensions	
Height (A)	72 mm
Width (B)	72 mm
Depth (C)	114 mm

Dimensions

Front View



Side View



Wiring diagram



Probe input:

- NTC

Vemer S.p.A. declines all responsibility for the use of the products for purposes other than those for which they are intended, as indicated in the technical documentation. Vemer S.p.A. reserves the right to make, without prior notice, such changes as may, in its sole discretion, improve the technical and functional characteristics of the products and the related production logic. The technical characteristics and images of the products indicated are given for information only and are not binding in any way, since they may be modified without prior notice.

Accessories compatible with the product

NTC C

VE123600

NTC C thermistor with a 2-wire NTC semiconductor sensor encased in eco-printed plastic for temperature detection, length 1.5 m

NTC BC

VE124400

NTC BC thermistor with a 2-wire NTC semiconductor sensor housed in eco-molded plastic and equipped with a cable, particularly suitable for measuring the temperature outside pipes; length: 1.5 m

NTC 3MT

VE152500

NTC RTD sensor, 2-wire, with NTC semiconductor for temperature measurement, 3 m length

NTC

VN870200

NTC RTD sensor, 2-wire, with NTC semiconductor for temperature measurement, 1.5 m length

Reference standards

Compliance with Community Directives:

• 2014/35/UE (LVD) • 2014/30/UE (EMCD) • 2011/65/UE e 2015/863/UE (ROHS)

is declared with reference to the following Standards:

• EN IEC 60730-2-9 • EN IEC 63000

Vemer S.p.A. declines all responsibility for the use of the products for purposes other than those for which they are intended, as indicated in the technical documentation. Vemer S.p.A. reserves the right to make, without prior notice, such changes as may, in its sole discretion, improve the technical and functional characteristics of the products and the related production logic. The technical characteristics and images of the products indicated are given for information only and are not binding in any way, since they may be modified without prior notice.