HT JK-2P3D

VM643400



[Model variant]

Digital panel-mounted temperature controller (33x75) for temperature control in both heating and cooling in applications such as ovens and burners. The device can be connected to type J, K, L, R, S, T, E, and N thermocouples.

General features

- Automatic cold junction compensation
- Possibility of selecting the probe type
- Password protection for stored settings
- Parameter setting in digital mode:
  - Set-point
  - Differential
  - Neutral zone
  - Output actuation times
  - Function and digital input delay time
  - Alarm delay time
  - Probe calibration OFFSET
  - Displayed resolution
  - Temperature measurement unit
  - Measurement display filter (refresh rate)
  - Probe input type
- Modes of operation (regulation)
  - ON/OFF heating or cooling (with or without Neutral Zone)
  - PWM Direct, Reverse and Neutral Zone action
  - ALARM
  - Cooling mode
  - Special mode
- Digital input with configurable function:
  - external alarm
  - ON/OFF regulation
  - probe selection to display
  - set-point switching
  - Direct/Reverse switching
- Acoustic and visual alarm signalling for:
  - external alarm (digital input)
  - probe alarm (malfunction)
  - minimum or maximum alarm

Technical specifications

Power supply	
Power supply	12 ÷ 24 Vac/Vdc (-10% ÷ +10%)

Vemer S.p.A. declines all responsibility for the use of the products for purposes other than those for which they are intended, as indicated in the technical documentation. Vemer S.p.A. reserves the right to make, without prior notice, such changes as may, in its sole discretion, improve the technical and functional characteristics of the products and the related production logic. The technical characteristics and images of the products indicated are given for information only and are not binding in any way, since they may be modified without prior notice.

Revision date: 2026-02-02

Power supply	
Frequency	50 / 60 Hz
Absorption	3 VA
Measure	
Temperature display resolution	0.1 (for values in the range -9.9 ÷ 99.9) °C 1 (for values <-9,9 and > 99.9) °C
Temperature measurement accuracy	± 0.5 % of full scale value ± 1 digit °C
Functions	
Keypad lock function	✓
Probe alarm buzzer	✓
Functional characteristics	
Temperature display range	-99 ÷ 999 (depending on probe selected) °C
Operating conditions	
Operating temperature range	0 ÷ 50 °C
Relative humidity	< 80% RH
Storage temperature range	-25 ÷ 70 °C
Viewing	
Display	Red LEDs
Digits number	3
Display range	-99 ÷ 999 °C *
Inputs	
Digital input	✓
No. digital inputs	1
Auxiliary input features	Configurable
Number of connectable probes	1
Type of connectable probes	J (Fe-CuNi) K (NiCr-Ni) L (Fe-CuNi) R (Pt13Rh-Pt) S (Pt10Rh-Pt) T (Cu-CuNi) E (NiCr-CuNi) N (NiCrSi-NiSi)
Outputs	
Relay number	2
Relay capacity at 250 Vac	8 A
Mechanical features	
Protection degree	IP54 (on the front) IP20 (on terminals)
Overall dimensions	
Height (A)	33 mm

Vemer S.p.A. declines all responsibility for the use of the products for purposes other than those for which they are intended, as indicated in the technical documentation. Vemer S.p.A. reserves the right to make, without prior notice, such changes as may, in its sole discretion, improve the technical and functional characteristics of the products and the related production logic. The technical characteristics and images of the products indicated are given for information only and are not binding in any way, since they may be modified without prior notice.

Overall dimensions	
Width (B)	75 mm
Depth (C)	81 mm

Dimensions

Front View



Side View



Wiring diagram



Probe input:

- TC

Product variants

HT JK-1P3D

VM641800

Digital panel-mounted temperature controller (33×75) connectable with J, K, L, R, S, T, E, N thermocouple probes, 12 ÷ 24 Vac/Vdc, digital input, with 1 relay

Vemer S.p.A. declines all responsibility for the use of the products for purposes other than those for which they are intended, as indicated in the technical documentation. Vemer S.p.A. reserves the right to make, without prior notice, such changes as may, in its sole discretion, improve the technical and functional characteristics of the products and the related production logic. The technical characteristics and images of the products indicated are given for information only and are not binding in any way, since they may be modified without prior notice.

Accessories compatible with the product

Fe-Co (J)

VJ44330000

2-wire J-type thermocouple for temperature detection, length 3 m

Cr-Al (K)

VJ44410000

2-wire type K thermocouple for temperature detection, length 3 m

Cr-Al 1200 (K)

VJ44900000

2-wire type K thermocouple for temperature detection, length 3 m

TM3 230/12

VE256400

Transformer with 230 Vac terminals, 3 VA power and 12 V secondary voltage

TM3 115/12

VE257200

Transformer with 115 Vac terminals, 3 VA power and 12 V secondary voltage

TM3 230/24

VE258000

Transformer with 230 Vac terminals, 3 VA power and 24 V secondary voltage

TM3 115/24

VE259800

Transformer with 115 Vac terminals, 3 VA power and 24 V secondary voltage

TM6 230/12

VE260600

Transformer with 230 Vac terminals, 6 VA power and 12 V secondary voltage

TM6 230/24

VE261400

Transformer with 230 Vac terminals, 6 VA power and 24 V secondary voltage

Reference standards

Compliance with Community Directives:

• 2014/35/UE (LVD) • 2014/30/UE (EMCD) • 2011/65/UE e 2015/863/UE (ROHS)

is declared with reference to the following Standards:

• EN IEC 60730-2-9 • EN IEC 63000

Vemer S.p.A. declines all responsibility for the use of the products for purposes other than those for which they are intended, as indicated in the technical documentation. Vemer S.p.A. reserves the right to make, without prior notice, such changes as may, in its sole discretion, improve the technical and functional characteristics of the products and the related production logic. The technical characteristics and images of the products indicated are given for information only and are not binding in any way, since they may be modified without prior notice.