Pt 1000

VJ44660000



Sensor for temperature detection. Designed for fast response and built according to criteria ensuring high reliability and long-term durability.
Transmitted signal: Ω

General features

- Terminal: sensor in AISI 304 stainless steel capsule
- The cable outlet from the capsule is protected by a stainless steel spring.
- To extend the probe cable, use a bipolar cable with 1.5 mm² cross-section
- 3-wire resistance thermometer

Technical specifications

Measure	
Accuracy	Class B (IEC 751)
Functional characteristics	
Sensor type	Platinum resistance temperature sensor
Sensor working range	-40 ÷ 200 °C
Working range sensor + cable	-40 ÷ 200 °C
Mechanical features	
Protection degree	IP40
Physical features	
Cable type	Silicone
Diameter dimension	
Dimension Ø - A	6 mm
Dimensions	
Probe length	40 mm
Cable length	1.5 m

Vemer S.p.A. declines all responsibility for the use of the products for purposes other than those for which they are intended, as indicated in the technical documentation. Vemer S.p.A. reserves the right to make, without prior notice, such changes as may, in its sole discretion, improve the technical and functional characteristics of the products and the related production logic. The technical characteristics and images of the products indicated are given for information only and are not binding in any way, since they may be modified without prior notice.

Revision date: 2026-02-02

Pt 1000

VJ44660000

Dimensions

Total View



Reference standards

Compliance with Community Directive:

• **2011/65/UE e 2015/863/UE (ROHS)**

is declared by reference to the following Standard:

• **EN IEC 63000**

Vemer S.p.A. declines all responsibility for the use of the products for purposes other than those for which they are intended, as indicated in the technical documentation. Vemer S.p.A. reserves the right to make, without prior notice, such changes as may, in its sole discretion, improve the technical and functional characteristics of the products and the related production logic. The technical characteristics and images of the products indicated are given for information only and are not binding in any way, since they may be modified without prior notice.

Revision date: 2026-02-02