DP6040-06 UL

SA53290099



Series of insulators suitable for use as supports or spacers for electrically active parts such as busbars used in the construction of electrical panels. Made of polyamide with added glass fibres, they ensure long-term mechanical and electrical resistance. The material is halogen-free and UL V0 approved. The insulators feature a female threaded insert in brass or white galvanised steel on both support sides, allowing coupling with the relevant parts via special headless screws. The central band, depending on the model, is octagonal or hexagonal and allows fastening.

Technical specifications

Functional characteristics	
Arc resistance	> 180 s - ASTM D-495
Tracking resistance	3 W/min - ASTM D-2302
Operating voltage	1000 AC / DC (V)
Minimum internal discharge voltage	40 AC (kV)
Rated withstand voltage at 50 Hz for 1 min	12 kV
Operating conditions	
Operating temperature range	-40 ÷ 130 °C
Approvals and certifications	
UL approval	✓
Mechanical features	
Water absorption	< 0,2% - ASTM D-570
Tensile stress	1300 daN
Bending stress	750 daN
Compressive stress	8300 daN
Physical features	
Color	Black
Material class	Self-extinguishing, class V0 (1.6 mm) according to UL-94 standard
Halogen free	✓
Material	Polyamide
Overall dimensions	
Height (A)	40 mm
Width (B)	46 mm

Vemer S.p.A. declines all responsibility for the use of the products for purposes other than those for which they are intended, as indicated in the technical documentation. Vemer S.p.A. reserves the right to make, without prior notice, such changes as may, in its sole discretion, improve the technical and functional characteristics of the products and the related production logic. The technical characteristics and images of the products indicated are given for information only and are not binding in any way, since they may be modified without prior notice.

Other dimensions	
Dimension - D	11 mm
Diameter dimension	
Dimension Ø - A	40 mm
Dimension Ø - B	M6 mm
Dimensions	
Shape	Hexagonal

Dimensions

Total View



Product variants

DP6020-06 UL
SA51620099

DP6026-06 UL
SA52040099

DP6030-06 UL
SA52120099

DP8035-06 UL
SA52460099

DP6035-06 UL
SA52530099

DP6036-06 UL
SA52950099

DP8045-06 UL
SA53600099

DP6050-06 UL
SA54360099

DP6063-06 UL
SA55500099

Reference standards

Compliance with Community Directives:

• 2014/35/UE (LVD) • 2011/65/UE e 2015/863/UE (ROHS)

is declared with reference to the following Standards:

• EN IEC 61439-1 • EN IEC 63000

Vemer S.p.A. declines all responsibility for the use of the products for purposes other than those for which they are intended, as indicated in the technical documentation. Vemer S.p.A. reserves the right to make, without prior notice, such changes as may, in its sole discretion, improve the technical and functional characteristics of the products and the related production logic. The technical characteristics and images of the products indicated are given for information only and are not binding in any way, since they may be modified without prior notice.

TECHNICAL GUIDE

ELECTRODYNAMIC FORCES BETWEEN CONDUCTORS

Nomogram 1

Determination of force **F** per unit length

Required data: I = short-circuit current
D = distance between phases

Example: Isc = 15 kA (AC) D = 7 cm

result obtained from the nomogram: F ≅ 150 daN/m



Nomogram 2

Determinaton of distance **L** between supports

Required data: F = force per unit length
(obtained from the previous nomogram)
W = longitudinal and transverse section modulus of the busbars according to X-X oppure Y-Y respectively
(obtainable based on the dimensions and arrangement of the busbar, whether horizontal or vertical)

Example: F ≅ 150 daN/m W = 0,5 cm³
(50 x 8 vertical arrangement)

result obtained deducibile dal nomogramma: L ≅ 0,7 m



Nomogram 3

Determination of the minimum cantilever breaking load **P**

Required data: F = force per unit length
L = distance between supports (obtained from the previous nomogram)

Esempio: F ≅ 150 daN/m L ≅ 0,7 m (vertical arrangement)
result obtained from the nomogram:
P ≅ 500 daN
(for vertically arranged busbar system)

Once the value of load P is determined, the suitable insulator can be identified by checking the specific tables for each item (cantilever breaking load columns) for a value greater than or equal to the one obtained from Nomogram 3.



Vemer S.p.A. declines all responsibility for the use of the products for purposes other than those for which they are intended, as indicated in the technical documentation. Vemer S.p.A. reserves the right to make, without prior notice, such changes as may, in its sole discretion, improve the technical and functional characteristics of the products and the related production logic. The technical characteristics and images of the products indicated are given for information only and are not binding in any way, since they may be modified without prior notice.