C10/G

VE499000



Chemical spray product for installation and maintenance of electromechanical, electrical and electronic equipment

General features

- Pressurized container. Protect from sunlight and do not expose to temperatures above 50 °C. Do not pierce or burn even after use
- Do not spray on flames or hot surfaces
- Keep away from any source of combustion. Do not smoke
- Keep out of the reach of children
- Do not inhale gases, fumes, vapours, or aerosols
- Avoid accumulation of electrostatic charges
- Use only in a well-ventilated area
- Yellow marking paint. 100% acrylic enamel for horizontal and vertical signage. Suitable for construction site marking, various indications, industrial flooring, concrete, sand, etc.

Technical specifications

Physical features	
Color	Yellow
Dimensions	
Size	400 ml

Product variants

C10/R
VE500500
Red marking paint

C10/B
VE498200
Blue marking paint

C10/N
VE502100
Black marking paint

Vemer S.p.A. declines all responsibility for the use of the products for purposes other than those for which they are intended, as indicated in the technical documentation. Vemer S.p.A. reserves the right to make, without prior notice, such changes as may, in its sole discretion, improve the technical and functional characteristics of the products and the related production logic. The technical characteristics and images of the products indicated are given for information only and are not binding in any way, since they may be modified without prior notice.

Revision date: 2026-02-02

Safety Warnings



• H222 • H229 • H315 • H319 • H336 • P102 • P210 • P211 • P251 • P261 • P410+P412

H222 - Extremely flammable aerosol.
H229 - Pressurised container: may burst if heated.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H336 - It may cause somnolence or dizziness.
P102 - Keep out of the reach of children.
P210 - Keep away from heat sources, hot surfaces, sparks, open flames or other ignition sources. Do not smoke.
P211 - Do not spray on an open flame or other source of ignition.
P251 - Do not puncture or burn, even after use.
P261 - Avoid breathing dust / fumes / gases / mist / vapours / aerosols.
P410+P412 - Protect from sunlight. Do not expose to temperatures above 50 °C / 122 °F.

Vemer S.p.A. declines all responsibility for the use of the products for purposes other than those for which they are intended, as indicated in the technical documentation. Vemer S.p.A. reserves the right to make, without prior notice, such changes as may, in its sole discretion, improve the technical and functional characteristics of the products and the related production logic. The technical characteristics and images of the products indicated are given for information only and are not binding in any way, since they may be modified without prior notice.