# Athena.Temp

VN942900






Wall-mounted remote temperature probe for Athena smart thermostat. The selector switch on the front allows a temperature offset to be set in relation to the setpoint set on Athena. The detected temperature and the set offset are communicated to Athena via cable (RS-485 bus). The device has an LED for low battery signaling.

## Technical specifications

| | |
|---|---|
| **Power supply** | |
| Power supply | 2 batteries (AAA)<br>1.5 V<br>Alkaline<br>NOT rechargeable |
| Battery autonomy | 12 months |
| **Temperature settings** | |
| Temperature setting range | 0 ÷ 40 °C |
| **Measure** | |
| Temperature measuring range | 0 ÷ 40 °C |
| **Physical features** | |
| Device command | Knob |

## Wiring diagram




### Reference standards

Compliance with Community Directives:

**• 2014/35/UE (LVD) • 2014/30/UE (EMCD) • 2011/65/UE e 2015/863/UE (ROHS)**

is declared with reference to the following Standards:

**• EN IEC 60730-2-9 • EN IEC 63000**

Vemer S.p.A. declines all responsibility for the use of the products for purposes other than those for which they are intended, as indicated in the technical documentation. Vemer S.p.A. reserves the right to make, without prior notice, such changes as may, in its sole discretion, improve the technical and functional characteristics of the products and the related production logic. The technical characteristics and images of the products indicated are given for information only and are not binding in any way, since they may be modified without prior notice.



Revision date: 2026-02-02