Energy-230R TAi

VE012100



Static energy meter for displaying active energy consumption in single-phase 230 Vac systems. 230 Vac power supply for panel-mounted devices (72×72 mm), with electromechanical counter and pulse output. Current input via external x/5 A CTs.

General features

- Green LED: power presence
- Red blinking LED: indicates active energy consumption (each blink = 1/16 kWh)
- Selector for transformation ratio: CT selection via dip-switches located under the front cover
- 7-digit electromechanical counter
- Static meter with amperometric connection via CT x/5 A
- Selectable CT ratios via dip-switch, from 5 A up to 1000 A
- Pulse output for PC display of consumed energy via dedicated software and the corresponding concentrator module
- Galvanically isolated amperometric input (CT secondary may be grounded)

Technical specifications

Power supply	
Power supply	230 Vac (-15% ÷ +10%)
Frequency	50 / 60 Hz
Measure	
Energy display resolution	1 kWh
Active energy measurement accuracy	Class 1 (EN IEC 62053-21)
Voltage circuit absorption	<2,5 VA
Current circuit absorption	< 2,5 VA

Vemer S.p.A. declines all responsibility for the use of the products for purposes other than those for which they are intended, as indicated in the technical documentation. Vemer S.p.A. reserves the right to make, without prior notice, such changes as may, in its sole discretion, improve the technical and functional characteristics of the products and the related production logic. The technical characteristics and images of the products indicated are given for information only and are not binding in any way, since they may be modified without prior notice.

Revision date: 2026-02-02

Measure	
AC current range	5 A 10 A 25 A 50 A 75 A 100 A 125 A 150 A 200 A 250 A 300 A 400 A 500 A 600 A 800 A 1000 A
Type of insertion - current	Via external CT x/5
Starting current	< 15 mA
Nominal - rated current	5 A
Maximum current	6 A
Operating conditions	
Operating temperature range	-10 ÷ 45 °C
Relative humidity	10% ÷ 90% non-condensing RH
Storage temperature range	-25 ÷ 70 °C
Viewing	
Features of electromechanical counter	7 digits
Digits number	7
Viewing	Electromechanical counter
Outputs	
Optoisolated pulse output	✓
Pulse weight	1 kWh
Pulse duration	100 ms
Pulse output current	< 20 mA
Output pulse voltage	9 ÷ 24 Vdc
Mechanical features	
Protection degree	IP20
Overall dimensions	
Height (A)	72 mm
Width (B)	72 mm
Depth (C)	105 mm

Vemer S.p.A. declines all responsibility for the use of the products for purposes other than those for which they are intended, as indicated in the technical documentation. Vemer S.p.A. reserves the right to make, without prior notice, such changes as may, in its sole discretion, improve the technical and functional characteristics of the products and the related production logic. The technical characteristics and images of the products indicated are given for information only and are not binding in any way, since they may be modified without prior notice.

Dimensions

Front View



Side View



Wiring diagram



Graphic details



Warning: the secondary circuits of current transformers MUST NOT be connected to earth.

Accessories compatible with the product

CLIP-485

VN905600

Energy series concentrator module for meters

LAN-485

VE304200

LAN/RS-485 interface + software (on request)

Energy-View

VN970000

System consisting of a USB/RS-485 interface and software for energy meters

Vemer S.p.A. declines all responsibility for the use of the products for purposes other than those for which they are intended, as indicated in the technical documentation. Vemer S.p.A. reserves the right to make, without prior notice, such changes as may, in its sole discretion, improve the technical and functional characteristics of the products and the related production logic. The technical characteristics and images of the products indicated are given for information only and are not binding in any way, since they may be modified without prior notice.

Reference standards

Compliance with Community Directives:

• 2014/35/UE (LVD) • 2014/30/UE (EMCD) • 2011/65/UE e 2015/863/UE (ROHS)

is declared with reference to the following Standards:

• EN 61010-1 • EN IEC 62052-11 • EN IEC 62053-21 • EN IEC 63000

Vemer S.p.A. declines all responsibility for the use of the products for purposes other than those for which they are intended, as indicated in the technical documentation. Vemer S.p.A. reserves the right to make, without prior notice, such changes as may, in its sole discretion, improve the technical and functional characteristics of the products and the related production logic. The technical characteristics and images of the products indicated are given for information only and are not binding in any way, since they may be modified without prior notice.